

MIFARE Mullion Readers

5002-1630 Enterprise Reader

Stylish and fully featured MIFARE® readers from TDSi.

A stylish and full featured range of mullion readers from TDSi featuring MIFARE technologies.

TDSi is pleased to offer high quality mullion readers in robust polycarbonate housings with excellent read range.



Features and Benefits.

Compatible with ISO 14443-A standard for 13.56MHz

One card for all applications including cashless vending.

Fully encapsulated design

Provides maximum protection against water ingress making it suitable for mounting both indoor and out.

Integral LEDs

Provides clear visual indication of access status.

In-built sounder

Gives unambiguous feedback of card reads.

Choice of output options

Allows connection to the majority of access control systems.

Part No.	5002-1630
Dimension	45 x 130 x 17mm
Weight	250g
Operating Environment	-20°C to +55°C, 0 to 95% RH (non-condensing)
Power Supply	7 to 14VDC, 200mA (Max)
Operating Frequency	13.56MHz (nominal)
Card Technology	MIFARE Classic, Plus, DESfire EV
Sounder	Integral
LED's	RGB
Read Range*	< 55mm
Ingress Protection	IP65
Impact Protection	IK07
Output Formats	Magnetic Stripe, Wiegand 26-bit** / 34-bit / 37 bit

Dimensions



Ordering Information

Part Number: 5002-1630

Description: TDSi MIFARE Classic, Plus, DESfire EV1, EV2, EV3 (Standard Mode)

*Figures may vary between cards and installation

**As standard. Contact TDSi for alternative configurations